3212-8000 Series

Network Video Recorder



3212-8000 Front

Key Features

- Face and temperature recognition when used with 3212-2000
- Up to 16 recognition groups with 10,000 face images in total
- Smart Search by temperature and face
- 1 10M/100M/1000M network interface
- Multiple PoE Ports
- Simultaneous HDMI and VGA Output



3212-8000 Rear

The CostarHD 3212-8000 AI NVR is a powerful appliance for the 3212-2000 Thermal Imaging Radiometric Detection Camera. This Al appliance supports up to 4 of these cameras with power, recording and an intuitive GUI.

The 3212-8000 can process up to 20 face pictures per second allowing for a steady stream of scans in rapid succession.

Offered in a 3TB and 6TB option the flexible storage options will allow you to store as much or a little footage as you desire. The integrated Power over Ethernet (PoE) switch allows for a quick, simple, and effortless installation between the camera and the AI NVR.

When used as a workstation the 3212-8000 serves as the main processing unit for thermal cameras that offers temperature reports and ways to viewing capabilities. The HDMI and USB connections allow for the 3212-8000 to function as a monitoring station for system operators.















3212-8000 Series

Network Video Recorder



VIDEO OUTPUT

HDMI Output 3840×2160,1920×1080, 1440×900, 1280×1024

VGA Output 1920×1080,1440×900,

1280×1024

Dual Stream Support

Multi-Screen Display Mirrored displays with up to

4 video panes

AI RECOGNITIONS

Body Temp-filter Real-time body temperature

screening and display temperature recording and

over temperature snapshots

Trigger Events Buzzer, Alarm prompt, Email,

Alarm Out

FACE RECOGNITION

Stranger Mode Detect strangers' faces (not

in device's face database) Similarity threshold can be

set manually

Database Up to 16 face groups with Management 10,000 face images in total Database All data can be applied to

Application any channel

BODY TEMP-FILTER

Temperature Real-time display of

temperature measurement

results

Smart Search Time, Person Type,

Temperature Type, ID

MULTI-OBJECTIVE

Face Real-time captured and

display faces comparison

results

RECORDING

Record Mode Manual, Schedule

(Regular, Continuous), Event

Trigger Events Motion Detection,

Video Loss, Alarm in

PLAYBACK AND BACKUP

Sync Playback 4/1

Search Mode Time/Date, Alarm,

Picture grid, Event

Backup Mode USB Device, Network, eSATA

NETWORK

PoE

Interface 1 RJ-45 port

(10/100/1000Mbps) 16 ports (IEEE 802.3af),

128W

Network Function HTTP, HTTPS, TCP/IP, IPv4,

UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, IP Filter, DDNS, 802.1X, SNMP, PPPoE

Remote Users 8 users

Interoperability ONVIF, SDK, CGI

STORAGE

Internal HDD 2 SATA ports, up to 3TB each

eSATA 1 eSATA port Cloud Storage Support

INTERFACE

Audio I/O 1 Input, 1 Output

Alarm Input 2 Inputs
Alarm Output 2 Outputs

USB 3 ports (USB 2.0 x2,

USB 3.0 x1)

ELECTRICAL

Power Supply 100~240VAC,

max output 300W

Power Consumption < 15W (without HDD)

MECHANICAL

Dimensions $440(W) \times 368.3(D) \times 70(H)$ mm

 $17.3(W) \times 14.5(D) \times 2.8(H)$ in.

Net Weight 12.74lbs. (5.78kg)

ENVIRONMENTAL

Operating Temp. $-10 \sim 50^{\circ}\text{C} (14 \sim 122^{\circ}\text{F})$ Storage Conditions Less than 90% RH

storage contamions Less than 507

CERTIFICATIONS


CE, FCC

ORDERING INFORMATION

3212-8003 3TB NVR with Integrated PoE Switch **3212-8006** 6TB NVR with Integrated PoE Switch

3212-2000 DIMENSIONS

Dimension	3212-8000	
	Inches	mm
Α	17.3	440
В	14.5	368.3
С	2.8	70





About CostarHD™